

**SPACE Q LED1X3500 J247 T840 OP • 1120692**



Product:	Space Q LED1x3500 J247 T840 OP
Order code:	1120692
Family:	Space Q LED
Product group:	Recessed luminaires

**GENERAL DATA**

<b>Description:</b>	Recessed mounted decorative LED luminaire Light distribution type: direct Optical system: opal PMMA diffuser Housing: steel Colour: white (RAL9016)
<b>Installation:</b>	In modular suspended ceilings. Push-in terminal, 2x1x1.5mm2
<b>Environment:</b>	Indoor
<b>Application:</b>	office, education, corridor, retail, public place

**ELECTRICAL DATA**

<b>Mains voltage:</b>	220-240V, 50/60Hz	<b>System power*, W:</b>	36
<b>Control gear:</b>	ECG on/off	<b>Integrated sensor:</b>	None
<b>Connection:</b>	Push-in terminal, 2x1x1.5mm2		

**LIGHTING DATA**

<b>Light source and cap, W:</b>	LED	<b>Light source included:</b>	yes
<b>Luminaire output*, lm(ta+25°C):</b>	3500	<b>System efficacy, lm/W:</b>	97
<b>CRI (Ra):</b>	80+	<b>CCT, K:</b>	4000
<b>SDCM:</b>	5	<b>Distribution Type:</b>	Direct
<b>LED lifetime, h:</b>	50000/L70B50		


**TECHNICAL DATA**

<b>Net weight, kg:</b>	2	<b>Quantity in package, pcs:</b>	1
<b>Packaging volume, m3/pcs:</b>	0.0309		
<b>Dimensions, mm:</b>	595x595x83		

**STANDARDS**

<b>Operating temperature range, °C:</b>	ta 0...+35	<b>Protection class IEC:</b>	II
<b>Ingress protection code:</b>	IP40	<b>Mechanical impact resistance:</b>	IK02
<b>EEC:</b>	E	<b>Certificates:</b>	CE, UKCA, RoHS
<b>Warranty:</b>	3 years (5 years - see warranty Ts and Cs)		

Light distribution curve (.jpg)



**Note:**

Tolerance range for optical and electrical data:  $\pm 10\%$ . Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2023-11-02 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ [info@northcliffe.org](mailto:info@northcliffe.org) ■ [www.northcliffe.org](http://www.northcliffe.org)