


BALI C LED

Recessed Luminaires



Description:

Recessed mounted frameless LED luminaire
 Light distribution type: direct
 Optical system: opal PMMA diffuser
 Housing: steel
 Colour: white (RAL9003)

General data:

Mains voltage: 220-240V, 50/60Hz
 LED lifetime, h: 100000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP20
 Operating temperature range, °C: ta 0...+35

Installation:

In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 3x2x2.5mm2

Environment:

Indoor

Application:

Office, education, corridor, retail, public place


Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI* (Ra)	CCT*, K	Weight, kg
BALI C LED1x1800 D103 T840 OP LT80	300	300	142	1764	16,4	108	80+	4000	2,5
BALI C LED1x2450 D104 T840 OP LT80	300	300	142	2424	23,5	103	80+	4000	2,5
BALI C LED1x3600 D105 T840 OP LT80	450	450	142	3566	32	111	80+	4000	4,8
BALI C LED1x4150 D106 T840 OP LT80	450	450	142	4121	37,7	109	80+	4000	4,8
BALI C LED1x5300 D107 T840 OP LT80	600	600	152	5291	46,5	114	80+	4000	7,5
BALI C LED1x7300 D108 T840 OP LT80	600	600	152	7273	66,6	109	80+	4000	7,5
BALI C LED1x8850 D109 T840 OP LT80	900	900	152	8835	79,8	111	80+	4000	10,5
BALI C LED1x11700 D110 T840 OP LT80	900	900	152	11657	108	108	80+	4000	10,5

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

T830	Colour temperature 3000K, CRI 80+	MW	Integrated microwave (MW) motion sensor with on-off control
T840	Colour temperature 4000K, CRI 80+	EM3	Emergency version 3 hours
OP LT80	Opal diffuser with high light transmittance	EM3B	Emergency version 3 hours (best available technology)
OP TP(a)	TP(a) rated termoplastic opal diffuser	EM3A	Emergency version equipped with an autonomous testing system, 3 hours
DALI	Driver with DALI interface and switch-control dimming	EM3D	Emergency version 3 hours with DALI interface
BLT	Integrated wireless control unit and driver for lighting control via mobile device (via Bluetooth)		

OP LT80



Applications:

