


JETTA R LED

Recessed Luminaires



Description: Recessed mounted decorative LED luminaire
 Light distribution type: indirect
 Optical system: white perforated steel louver with soft light distribution, opal polycarbonate film
 Housing: steel
 Colour: white (RAL9003)

General data: Mains voltage: 220-240V, 0/50/60Hz
 LED lifetime, h: 100000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP20
 Mechanical impact resistance: IK02
 Operating temperature range, °C: ta 0...+35

Installation: In modular suspended ceilings (600), in ceilings with cut-out openings (mounting frame to be ordered separately). Push-in terminal, 3x2x2.5mm2

Environment: Indoor

Application: Office, education, corridor, retail, public place


Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI * (Ra)	CCT*, K	Weight, kg
Jetta R LED1x2900 G359 T830	595	595	125	2746	26,5	104	80+	3000	3,75
Jetta R LED1x3700 G360 T830	595	595	125	3471	34,5	101	80+	3000	3,75
Jetta R LED1x4200 G361 T830	595	595	125	3980	41,0	97	80+	3000	3,75
Jetta R LED1x2900 G359 T840	595	595	125	2895	26,5	109	80+	4000	3,75
Jetta R LED1x3700 G360 T840	595	595	125	3658	34,5	106	80+	4000	3,75
Jetta R LED1x4200 G361 T840	595	595	125	4194	41,0	102	80+	4000	3,75

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

T830	Colour temperature 3000K, CRI 80+	EM3A	Emergency version equipped with an autonomous testing system, 3 hours
T840	Colour temperature 4000K, CRI 80+	EM3D	Emergency version 3 hours with DALI interface
DALI	Driver with DALI interface and switch-control dimming	WIE3	3-pole "Wieland - gesis classic" type or compatible connector
BLT	Integrated wireless control unit and driver for lighting control via mobile device (via Bluetooth)	WIE5	5-pole "Wieland - gesis classic" type or compatible connector
COR	Driver with Corridor function (never off)	WIESD	5-pole DALI "Wieland - gesis classic" type or compatible connector
COR1min	Driver with Corridor function 1min (switch off after 1 min.)	Schuko-1.5m	3-pole "Schuko" type plug with 3x1.0mm ² 1.5m cable
COR30min	Driver with Corridor function 30min (switch off after 30 min.)	Schuko-3.0m	3-pole "Schuko" type plug with 3x1.0mm ² 3.0m cable
EM3	Emergency version 3 hours		
EM3B	Emergency version 3 hours (best available technology)		

STANDARD



Available accessories:



Product: Recessed MTG FRAME S626x626 RAL9003
Description: Frame for LED luminaire 595x595mm installation into plasterboard ceiling (1pcs), white steel

Application:

