


## WING D LED

### Recessed Luminaires



**Images for the product family and options:**



**Description:** Recessed mounted LED luminaire  
 Light distribution: direct/indirect  
 Optical system: translucent micro-prismatic PMMA diffuser  
 Housing: steel  
 Colour: white (RAL9003)

**General data:** Mains voltage: 220-240V, 0/50/60Hz  
 LED lifetime, h: 100000/L80B50  
 SDCM: 3  
 Protection class IEC: I  
 Ingress protection code: IP40/20  
 Mechanical impact resistance: IK05  
 Operating temperature range, °C: ta 0...+35

**Installation:** In modular suspended ceilings (600/625), in ceilings with cut-out openings (mounting frame to be ordered separately). Push-in terminal, 3x2x2.5mm<sup>2</sup>

**Environment:** Indoor


**Application:** Office, education, corridor, retail, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI* (Ra)	CCT*, K	Weight, kg
Wing D LED2x1750 G362 T830 MPRZ LT92	595	595	96	3244	24,5	132	80+	3000	3,8
Wing D LED2x2350 G363 T830 MPRZ LT92	595	595	96	4415	34,5	128	80+	3000	3,8
Wing D LED2x1750 G362 T840 MPRZ LT92	595	595	96	3419	24,5	140	80+	4000	3,8
Wing D LED2x2350 G363 T840 MPRZ LT92	595	595	96	4678	34,5	136	80+	4000	3,8
Wing D LED2x1750 G364 T830 MPRZ LT92 W625	622	622	96	3244	24,5	132	80+	3000	3,9
Wing D LED2x2350 G365 T830 MPRZ LT92 W625	622	622	96	4415	33	134	80+	3000	3,9
Wing D LED2x1750 G364 T840 MPRZ LT92 W625	622	622	96	3419	24,5	140	80+	4000	3,9
Wing D LED2x2350 G365 T840 MPRZ LT92 W625	622	622	96	4678	33	142	80+	4000	3,9

\*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

**Available options:**

T830	Colour temperature 3000K, CRI 80+	EM3	Emergency version 3 hours
T840	Colour temperature 4000K, CRI 80+	EM3B	Emergency version 3 hours (best available technology)
MPRZ LT92	Translucent micro-prismatic diffuser with high light Transmittance	EM3A	Emergency version equipped with an autonomous testing system, 3 hours
OP TP(a)	TP(a) rated termoplastic opal diffuser	EM3D	Emergency version 3 hours with DALI interface
DALI	Driver with DALI interface and switch-control dimming	WIE3	3-pole "Wieland - gesis classic" type or compatible connector
BLT	Integrated wireless control unit and driver for lighting control via mobile device (via Bluetooth)	WIE5	5-pole "Wieland - gesis classic" type or compatible connector
TW	Integrated light source and driver for Tuneable white control 2700-6500 K	WIE5D	5-pole DALI "Wieland - gesis classic" type or compatible connector
BLT TW	Integrated light source, wireless control unit and driver for Tuneable white control 2700-6500 K via mobile device (via Bluetooth)	Schuko-1.5m	3-pole "Schuko" type plug with 3x1.0mm <sup>2</sup> 1.5m cable
COR	Driver with Corridor function (never off)	Schuko-3.0m	3-pole "Schuko" type plug with 3x1.0mm <sup>2</sup> 3.0m cable
COR1min	Driver with Corridor function 1min (switch off after 1 min.)	RAL	RAL colour
COR30min	Driver with Corridor function 30min (switch off after 30 min.)		



**Available accessories:**



Product: Recessed MTG FRAME S626x626 RAL9003  
Description: Frame for LED luminaire 595x595mm installation into plasterboard ceiling (1pcs), white steel

### Applications:

