


BORA Z LED

Continuous Line and Batten Luminaires



Images for the product family and options:



Description: Mounted across cable trays batten LED luminaire
 Light distribution type: direct
 Optical system: lenses
 Housing: zinc coated steel
 Colour: light grey

General data: Mains voltage: 220-240V, 0/50/60Hz
 LED lifetime, h: 100000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP23
 Mechanical impact resistance: IK07
 Operating temperature range, °C: ta -10...+35/+40

Installation: Across cable trays (adjustable mounting brackets included). Push-in terminal, 5x2x2.5mm2

Environment: Indoor

Application: Retail, industry, warehouse, hall, public place



Adjustable hanger support brackets for luminaire installation across cable trays. Each end can be extended 420mm, transforming luminaire to fit a specific installation arrangement

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Bora Z LED 1x5550 G634 T830 L30 HSB	1606-2446	75	118	5185	30,0	173	80+	3000	4,40
Bora Z LED 1x6600 G635 T830 L30 HSB	1606-2446	75	118	6165	35,9	172	80+	3000	4,40
Bora Z LED 1x7600 G636 T830 L30 HSB	1606-2446	75	118	7092	41,6	170	80+	3000	4,40
Bora Z LED 1x6950 G637 T830 L30 HSB	1906-2746	75	118	6482	36,7	177	80+	3000	4,60
Bora Z LED 1x8250 G638 T830 L30 HSB	1906-2746	75	118	7707	44,4	173	80+	3000	4,60
Bora Z LED 1x9450 G639 T830 L30 HSB	1906-2746	75	118	8865	51,5	172	80+	3000	4,60
Bora Z LED 1x11050 G640 T830 L30 HSB	2746-3586	75	118	10370	58,1	178	80+	3000	5,00
Bora Z LED 1x13150 G641 T830 L30 HSB	2746-3586	75	118	12331	70,3	175	80+	3000	5,00
Bora Z LED 1x15150 G642 T830 L30 HSB	2746-3586	75	118	14184	82,4	172	80+	3000	5,00
Bora Z LED 1x13850 G643 T830 L30 HSB	3260-4100	75	118	12963	72,7	178	80+	3000	5,40
Bora Z LED 1x16450 G644 T830 L30 HSB	3260-4100	75	118	15413	87,0	177	80+	3000	5,40
Bora Z LED 1x18900 G645 T830 L30 HSB	3260-4100	75	118	17729	101,9	174	80+	3000	5,40

TECHNICAL DATA SHEET

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Bora Z LED 1x5550 G634 T840 L30 HSB	1606-2446	75	118	5465	30,0	182	80+	4000	4,40
Bora Z LED 1x6600 G635 T840 L30 HSB	1606-2446	75	118	6499	35,9	181	80+	4000	4,40
Bora Z LED 1x7600 G636 T840 L30 HSB	1606-2446	75	118	7475	41,6	179	80+	4000	4,40
Bora Z LED 1x6950 G637 T840 L30 HSB	1906-2746	75	118	6832	36,7	186	80+	4000	4,60
Bora Z LED 1x8250 G638 T840 L30 HSB	1906-2746	75	118	8123	44,4	183	80+	4000	4,60
Bora Z LED 1x9450 G639 T840 L30 HSB	1906-2746	75	118	9344	51,5	181	80+	4000	4,60
Bora Z LED 1x11050 G640 T840 L30 HSB	2746-3586	75	118	10931	58,1	188	80+	4000	5,00
Bora Z LED 1x13150 G641 T840 L30 HSB	2746-3586	75	118	12997	70,3	185	80+	4000	5,00
Bora Z LED 1x15150 G642 T840 L30 HSB	2746-3586	75	118	14950	82,4	181	80+	4000	5,00
Bora Z LED 1x13850 G643 T840 L30 HSB	3260-4100	75	118	13664	72,7	188	80+	4000	5,40
Bora Z LED 1x16450 G644 T840 L30 HSB	3260-4100	75	118	16247	87,0	187	80+	4000	5,40
Bora Z LED 1x18900 G645 T840 L30 HSB	3260-4100	75	118	18688	101,9	183	80+	4000	5,40
Bora Z LED 1x5550 G634 T830 L40x75 HSB	1606-2446	75	118	5185	30,0	173	80+	3000	4,40
Bora Z LED 1x6600 G635 T830 L40x75 HSB	1606-2446	75	118	6165	35,9	172	80+	3000	4,40
Bora Z LED 1x7600 G636 T830 L40x75 HSB	1606-2446	75	118	7092	41,6	170	80+	3000	4,40
Bora Z LED 1x6950 G637 T830 L40x75 HSB	1906-2746	75	118	6482	36,7	177	80+	3000	4,60
Bora Z LED 1x8250 G638 T830 L40x75 HSB	1906-2746	75	118	7707	44,4	173	80+	3000	4,60
Bora Z LED 1x9450 G639 T830 L40x75 HSB	1906-2746	75	118	8865	51,5	172	80+	3000	4,60
Bora Z LED 1x11050 G640 T830 L40x75 HSB	2746-3586	75	118	10370	58,1	178	80+	3000	5,00
Bora Z LED 1x13150 G641 T830 L40x75 HSB	2746-3586	75	118	12331	70,3	175	80+	3000	5,00
Bora Z LED 1x15150 G642 T830 L40x75 HSB	2746-3586	75	118	14184	82,4	172	80+	3000	5,00
Bora Z LED 1x13850 G643 T830 L40x75 HSB	3260-4100	75	118	12963	72,7	178	80+	3000	5,40
Bora Z LED 1x16450 G644 T830 L40x75 HSB	3260-4100	75	118	15413	87,0	177	80+	3000	5,40
Bora Z LED 1x18900 G645 T830 L40x75 HSB	3260-4100	75	118	17729	101,9	174	80+	3000	5,40
Bora Z LED 1x5550 G634 T840 L40x75 HSB	1606-2446	75	118	5465	30,0	182	80+	4000	4,40
Bora Z LED 1x6600 G635 T840 L40x75 HSB	1606-2446	75	118	6499	35,9	181	80+	4000	4,40
Bora Z LED 1x7600 G636 T840 L40x75 HSB	1606-2446	75	118	7475	41,6	179	80+	4000	4,40
Bora Z LED 1x6950 G637 T840 L40x75 HSB	1906-2746	75	118	6832	36,7	186	80+	4000	4,60
Bora Z LED 1x8250 G638 T840 L40x75 HSB	1906-2746	75	118	8123	44,4	183	80+	4000	4,60
Bora Z LED 1x9450 G639 T840 L40x75 HSB	1906-2746	75	118	9344	51,5	181	80+	4000	4,60
Bora Z LED 1x11050 G640 T840 L40x75 HSB	2746-3586	75	118	10931	58,1	188	80+	4000	5,00
Bora Z LED 1x13150 G641 T840 L40x75 HSB	2746-3586	75	118	12997	70,3	185	80+	4000	5,00
Bora Z LED 1x15150 G642 T840 L40x75 HSB	2746-3586	75	118	14950	82,4	181	80+	4000	5,00
Bora Z LED 1x13850 G643 T840 L40x75 HSB	3260-4100	75	118	13664	72,7	188	80+	4000	5,40
Bora Z LED 1x16450 G644 T840 L40x75 HSB	3260-4100	75	118	16247	87,0	187	80+	4000	5,40
Bora Z LED 1x18900 G645 T840 L40x75 HSB	3260-4100	75	118	18688	101,9	183	80+	4000	5,40
Bora Z LED 1x5550 G634 T830 L75 HSB	1606-2446	75	118	5240	30,0	175	80+	3000	4,40
Bora Z LED 1x6600 G635 T830 L75 HSB	1606-2446	75	118	6230	35,9	173	80+	3000	4,40
Bora Z LED 1x7600 G636 T830 L75 HSB	1606-2446	75	118	7166	41,6	172	80+	3000	4,40
Bora Z LED 1x6950 G637 T830 L75 HSB	1906-2746	75	118	6550	36,7	178	80+	3000	4,60
Bora Z LED 1x8250 G638 T830 L75 HSB	1906-2746	75	118	7788	44,4	175	80+	3000	4,60
Bora Z LED 1x9450 G639 T830 L75 HSB	1906-2746	75	118	8958	51,5	174	80+	3000	4,60
Bora Z LED 1x11050 G640 T830 L75 HSB	2746-3586	75	118	10480	58,1	180	80+	3000	5,00
Bora Z LED 1x13150 G641 T830 L75 HSB	2746-3586	75	118	12461	70,3	177	80+	3000	5,00
Bora Z LED 1x15150 G642 T830 L75 HSB	2746-3586	75	118	14333	82,4	174	80+	3000	5,00
Bora Z LED 1x13850 G643 T830 L75 HSB	3260-4100	75	118	13099	72,7	180	80+	3000	5,40
Bora Z LED 1x16450 G644 T830 L75 HSB	3260-4100	75	118	15576	87,0	179	80+	3000	5,40
Bora Z LED 1x18900 G645 T830 L75 HSB	3260-4100	75	118	17916	101,9	176	80+	3000	5,40
Bora Z LED 1x5550 G634 T840 L75 HSB	1606-2446	75	118	5523	30,0	184	80+	4000	4,40
Bora Z LED 1x6600 G635 T840 L75 HSB	1606-2446	75	118	6567	35,9	183	80+	4000	4,40
Bora Z LED 1x7600 G636 T840 L75 HSB	1606-2446	75	118	7554	41,6	181	80+	4000	4,40
Bora Z LED 1x6950 G637 T840 L75 HSB	1906-2746	75	118	6904	36,7	188	80+	4000	4,60
Bora Z LED 1x8250 G638 T840 L75 HSB	1906-2746	75	118	8209	44,4	185	80+	4000	4,60
Bora Z LED 1x9450 G639 T840 L75 HSB	1906-2746	75	118	9442	51,5	183	80+	4000	4,60
Bora Z LED 1x11050 G640 T840 L75 HSB	2746-3586	75	118	11046	58,1	190	80+	4000	5,00
Bora Z LED 1x13150 G641 T840 L75 HSB	2746-3586	75	118	13134	70,3	187	80+	4000	5,00
Bora Z LED 1x15150 G642 T840 L75 HSB	2746-3586	75	118	15108	82,4	183	80+	4000	5,00
Bora Z LED 1x13850 G643 T840 L75 HSB	3260-4100	75	118	13808	72,7	190	80+	4000	5,40
Bora Z LED 1x16450 G644 T840 L75 HSB	3260-4100	75	118	16418	87,0	189	80+	4000	5,40
Bora Z LED 1x18900 G645 T840 L75 HSB	3260-4100	75	118	18884	101,9	185	80+	4000	5,40
Bora Z LED 1x5550 G634 T830 L75W HSB	1606-2446	75	118	5240	30,0	175	80+	3000	4,40
Bora Z LED 1x6600 G635 T830 L75W HSB	1606-2446	75	118	6230	35,9	173	80+	3000	4,40
Bora Z LED 1x7600 G636 T830 L75W HSB	1606-2446	75	118	7166	41,6	172	80+	3000	4,40
Bora Z LED 1x6950 G637 T830 L75W HSB	1906-2746	75	118	6550	36,7	178	80+	3000	4,60
Bora Z LED 1x8250 G638 T830 L75W HSB	1906-2746	75	118	7788	44,4	175	80+	3000	4,60
Bora Z LED 1x9450 G639 T830 L75W HSB	1906-2746	75	118	8958	51,5	174	80+	3000	4,60
Bora Z LED 1x11050 G640 T830 L75W HSB	2746-3586	75	118	10480	58,1	180	80+	3000	5,00
Bora Z LED 1x13150 G641 T830 L75W HSB	2746-3586	75	118	12461	70,3	177	80+	3000	5,00
Bora Z LED 1x15150 G642 T830 L75W HSB	2746-3586	75	118	14333	82,4	174	80+	3000	5,00
Bora Z LED 1x13850 G643 T830 L75W HSB	3260-4100	75	118	13099	72,7	180	80+	3000	5,40
Bora Z LED 1x16450 G644 T830 L75W HSB	3260-4100	75	118	15576	87,0	179	80+	3000	5,40
Bora Z LED 1x18900 G645 T830 L75W HSB	3260-4100	75	118	17916	101,9	176	80+	3000	5,40

TECHNICAL DATA SHEET

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Bora Z LED 1x5550 G634 T840 L75W HSB	1606-2446	75	118	5523	30,0	184	80+	4000	4,40
Bora Z LED 1x6600 G635 T840 L75W HSB	1606-2446	75	118	6567	35,9	183	80+	4000	4,40
Bora Z LED 1x7600 G636 T840 L75W HSB	1606-2446	75	118	7554	41,6	181	80+	4000	4,40
Bora Z LED 1x6950 G637 T840 L75W HSB	1906-2746	75	118	6904	36,7	188	80+	4000	4,60
Bora Z LED 1x8250 G638 T840 L75W HSB	1906-2746	75	118	8209	44,4	185	80+	4000	4,60
Bora Z LED 1x9450 G639 T840 L75W HSB	1906-2746	75	118	9442	51,5	183	80+	4000	4,60
Bora Z LED 1x11050 G640 T840 L75W HSB	2746-3586	75	118	11046	58,1	190	80+	4000	5,00
Bora Z LED 1x13150 G641 T840 L75W HSB	2746-3586	75	118	13134	70,3	187	80+	4000	5,00
Bora Z LED 1x15150 G642 T840 L75W HSB	2746-3586	75	118	15108	82,4	183	80+	4000	5,00
Bora Z LED 1x13850 G643 T840 L75W HSB	3260-4100	75	118	13808	72,7	190	80+	4000	5,40
Bora Z LED 1x16450 G644 T840 L75W HSB	3260-4100	75	118	16418	87,0	189	80+	4000	5,40
Bora Z LED 1x18900 G645 T840 L75W HSB	3260-4100	75	118	18884	101,9	185	80+	4000	5,40
Bora Z LED 1x5550 G634 T830 L90W HSB	1606-2446	75	118	5240	30,0	175	80+	3000	4,40
Bora Z LED 1x6600 G635 T830 L90W HSB	1606-2446	75	118	6230	35,9	173	80+	3000	4,40
Bora Z LED 1x7600 G636 T830 L90W HSB	1606-2446	75	118	7166	41,6	172	80+	3000	4,40
Bora Z LED 1x6950 G637 T830 L90W HSB	1906-2746	75	118	6550	36,7	178	80+	3000	4,60
Bora Z LED 1x8250 G638 T830 L90W HSB	1906-2746	75	118	7788	44,4	175	80+	3000	4,60
Bora Z LED 1x9450 G639 T830 L90W HSB	1906-2746	75	118	8958	51,5	174	80+	3000	4,60
Bora Z LED 1x11050 G640 T830 L90W HSB	2746-3586	75	118	10480	58,1	180	80+	3000	5,00
Bora Z LED 1x13150 G641 T830 L90W HSB	2746-3586	75	118	12461	70,3	177	80+	3000	5,00
Bora Z LED 1x15150 G642 T830 L90W HSB	2746-3586	75	118	14333	82,4	174	80+	3000	5,00
Bora Z LED 1x13850 G643 T830 L90W HSB	3260-4100	75	118	13099	72,7	180	80+	3000	5,40
Bora Z LED 1x16450 G644 T830 L90W HSB	3260-4100	75	118	15576	87,0	179	80+	3000	5,40
Bora Z LED 1x18900 G645 T830 L90W HSB	3260-4100	75	118	17916	101,9	176	80+	3000	5,40
Bora Z LED 1x5550 G634 T840 L90W HSB	1606-2446	75	118	5523	30,0	184	80+	4000	4,40
Bora Z LED 1x6600 G635 T840 L90W HSB	1606-2446	75	118	6567	35,9	183	80+	4000	4,40
Bora Z LED 1x7600 G636 T840 L90W HSB	1606-2446	75	118	7554	41,6	181	80+	4000	4,40
Bora Z LED 1x6950 G637 T840 L90W HSB	1906-2746	75	118	6904	36,7	188	80+	4000	4,60
Bora Z LED 1x8250 G638 T840 L90W HSB	1906-2746	75	118	8209	44,4	185	80+	4000	4,60
Bora Z LED 1x9450 G639 T840 L90W HSB	1906-2746	75	118	9442	51,5	183	80+	4000	4,60
Bora Z LED 1x11050 G640 T840 L90W HSB	2746-3586	75	118	11046	58,1	190	80+	4000	5,00
Bora Z LED 1x13150 G641 T840 L90W HSB	2746-3586	75	118	13134	70,3	187	80+	4000	5,00
Bora Z LED 1x15150 G642 T840 L90W HSB	2746-3586	75	118	15108	82,4	183	80+	4000	5,00
Bora Z LED 1x13850 G643 T840 L90W HSB	3260-4100	75	118	13808	72,7	190	80+	4000	5,40
Bora Z LED 1x16450 G644 T840 L90W HSB	3260-4100	75	118	16418	87,0	189	80+	4000	5,40
Bora Z LED 1x18900 G645 T840 L90W HSB	3260-4100	75	118	18884	101,9	185	80+	4000	5,40
Bora Z LED 1x5550 G634 T830 L1A18 HSB	1606-2446	75	118	5131	30,0	171	80+	3000	4,40
Bora Z LED 1x6600 G635 T830 L1A18 HSB	1606-2446	75	118	6100	35,9	170	80+	3000	4,40
Bora Z LED 1x7600 G636 T830 L1A18 HSB	1606-2446	75	118	7017	41,6	168	80+	3000	4,40
Bora Z LED 1x6950 G637 T830 L1A18 HSB	1906-2746	75	118	6413	36,7	175	80+	3000	4,60
Bora Z LED 1x8250 G638 T830 L1A18 HSB	1906-2746	75	118	7626	44,4	172	80+	3000	4,60
Bora Z LED 1x9450 G639 T830 L1A18 HSB	1906-2746	75	118	8771	51,5	170	80+	3000	4,60
Bora Z LED 1x11050 G640 T830 L1A18 HSB	2746-3586	75	118	10261	58,1	177	80+	3000	5,00
Bora Z LED 1x13150 G641 T830 L1A18 HSB	2746-3586	75	118	12201	70,3	173	80+	3000	5,00
Bora Z LED 1x15150 G642 T830 L1A18 HSB	2746-3586	75	118	14034	82,4	170	80+	3000	5,00
Bora Z LED 1x13850 G643 T830 L1A18 HSB	3260-4100	75	118	12827	72,7	177	80+	3000	5,40
Bora Z LED 1x16450 G644 T830 L1A18 HSB	3260-4100	75	118	15251	87,0	175	80+	3000	5,40
Bora Z LED 1x18900 G645 T830 L1A18 HSB	3260-4100	75	118	17543	101,9	172	80+	3000	5,40
Bora Z LED 1x5550 G634 T840 L1A18 HSB	1606-2446	75	118	5408	30,0	180	80+	4000	4,40
Bora Z LED 1x6600 G635 T840 L1A18 HSB	1606-2446	75	118	6430	35,9	179	80+	4000	4,40
Bora Z LED 1x7600 G636 T840 L1A18 HSB	1606-2446	75	118	7396	41,6	178	80+	4000	4,40
Bora Z LED 1x6950 G637 T840 L1A18 HSB	1906-2746	75	118	6760	36,7	184	80+	4000	4,60
Bora Z LED 1x8250 G638 T840 L1A18 HSB	1906-2746	75	118	8038	44,4	181	80+	4000	4,60
Bora Z LED 1x9450 G639 T840 L1A18 HSB	1906-2746	75	118	9246	51,5	180	80+	4000	4,60
Bora Z LED 1x11050 G640 T840 L1A18 HSB	2746-3586	75	118	10816	58,1	186	80+	4000	5,00
Bora Z LED 1x13150 G641 T840 L1A18 HSB	2746-3586	75	118	12860	70,3	183	80+	4000	5,00
Bora Z LED 1x15150 G642 T840 L1A18 HSB	2746-3586	75	118	14793	82,4	180	80+	4000	5,00
Bora Z LED 1x13850 G643 T840 L1A18 HSB	3260-4100	75	118	13520	72,7	186	80+	4000	5,40
Bora Z LED 1x16450 G644 T840 L1A18 HSB	3260-4100	75	118	16076	87,0	185	80+	4000	5,40
Bora Z LED 1x18900 G645 T840 L1A18 HSB	3260-4100	75	118	18491	101,9	181	80+	4000	5,40
Bora Z LED 1x5550 G634 T830 L2A25 HSB	1606-2446	75	118	5240	30,0	175	80+	3000	4,40
Bora Z LED 1x6600 G635 T830 L2A25 HSB	1606-2446	75	118	6230	35,9	173	80+	3000	4,40
Bora Z LED 1x7600 G636 T830 L2A25 HSB	1606-2446	75	118	7166	41,6	172	80+	3000	4,40
Bora Z LED 1x6950 G637 T830 L2A25 HSB	1906-2746	75	118	6550	36,7	178	80+	3000	4,60
Bora Z LED 1x8250 G638 T830 L2A25 HSB	1906-2746	75	118	7788	44,4	175	80+	3000	4,60
Bora Z LED 1x9450 G639 T830 L2A25 HSB	1906-2746	75	118	8958	51,5	174	80+	3000	4,60
Bora Z LED 1x11050 G640 T830 L2A25 HSB	2746-3586	75	118	10480	58,1	180	80+	3000	5,00
Bora Z LED 1x13150 G641 T830 L2A25 HSB	2746-3586	75	118	12461	70,3	177	80+	3000	5,00
Bora Z LED 1x15150 G642 T830 L2A25 HSB	2746-3586	75	118	14333	82,4	174	80+	3000	5,00
Bora Z LED 1x13850 G643 T830 L2A25 HSB	3260-4100	75	118	13099	72,7	180	80+	3000	5,40
Bora Z LED 1x16450 G644 T830 L2A25 HSB	3260-4100	75	118	15576	87,0	179	80+	3000	5,40
Bora Z LED 1x18900 G645 T830 L2A25 HSB	3260-4100	75	118	17916	101,9	176	80+	3000	5,40

TECHNICAL DATA SHEET

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Bora Z LED 1x5550 G634 T840 L2A25 HSB	1606-2446	75	118	5523	30,0	184	80+	4000	4,40
Bora Z LED 1x6600 G635 T840 L2A25 HSB	1606-2446	75	118	6567	35,9	183	80+	4000	4,40
Bora Z LED 1x7600 G636 T840 L2A25 HSB	1606-2446	75	118	7554	41,6	181	80+	4000	4,40
Bora Z LED 1x6950 G637 T840 L2A25 HSB	1906-2746	75	118	6904	36,7	188	80+	4000	4,60
Bora Z LED 1x8250 G638 T840 L2A25 HSB	1906-2746	75	118	8209	44,4	185	80+	4000	4,60
Bora Z LED 1x9450 G639 T840 L2A25 HSB	1906-2746	75	118	9442	51,5	183	80+	4000	4,60
Bora Z LED 1x11050 G640 T840 L2A25 HSB	2746-3586	75	118	11046	58,1	190	80+	4000	5,00
Bora Z LED 1x13150 G641 T840 L2A25 HSB	2746-3586	75	118	13134	70,3	187	80+	4000	5,00
Bora Z LED 1x15150 G642 T840 L2A25 HSB	2746-3586	75	118	15108	82,4	183	80+	4000	5,00
Bora Z LED 1x13850 G643 T840 L2A25 HSB	3260-4100	75	118	13808	72,7	190	80+	4000	5,40
Bora Z LED 1x16450 G644 T840 L2A25 HSB	3260-4100	75	118	16418	87,0	189	80+	4000	5,40
Bora Z LED 1x18900 G645 T840 L2A25 HSB	3260-4100	75	118	18884	101,9	185	80+	4000	5,40

* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

- L30 Optics with 30° beam angle, narrow
- L40x75 Optics with 40x75° beam angle, high rack
- L75W Optics with 60° beam angle, medium
- L75 Optics with 75° beam angle, standard
- L90W Optics with 90° beam angle, wide
- L2A25 Optics with double asymmetric beam
- L1A18 Optics with asymmetric beam
- DALI Driver with DALI interface and switch-control dimming
- EM3 Emergency version 3 hours
- EM3B Emergency version 3 hours (best available technology)
- EM3A Emergency version equipped with an autonomous testing system, 3 hours

- EM3D Emergency version 3 hours with DALI interface
- *note - Operating temperature range for Luminaires with EM option, °C: ta 0...+35
- L1 Driver connected to L1 line
- L2 Driver connected to L2 line
- L3 Driver connected to L3 line
- 1G Strain relief for power supply cable
- 2G Strain relief for power supply cable, 2pcs
- T830 Colour temperature 3000K, CRI 80+
- T840 Colour temperature 4000K, CRI 80+
- T930 Colour temperature 3000K, CRI 90+
- T940 Colour temperature 4000K, CRI 90+
- HSB Adjustable hanger support brackets for luminaire installation across cable trays. Each end extends 180-600mm

