


CAPELLA LED

Emergency Lighting



Description: Recessed mounted LED emergency exit sign
 Light distribution type: omnidirectional
 Optical system: clear PMMA diffuser
 Housing: steel
 Colour: Grey (RAL 7045)
 Battery charging time: 24 hours (12 hours optional: AUT)
 Battery: NiCd (LiFePO₄ optional: AUT), deep discharge protection
 Recognition distance: 30 meters

General data: Mains voltage: 220-240V, 50/60Hz
 LED lifetime, h: 50000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP20
 Mechanical impact resistance: IK02
 Operating temperature range, °C: ta 0...+40

Installation: In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 4x2x2.5mm²

Environment: Indoor

Application: Emergency exit sign



Supplied with universal sticker.

Product	Length, mm	Width, mm	Height, mm	Illumination mode	Emergency operating time, h	Power in emergency mode, W*	CRI *	CCT, K*	Weight, kg
Capella 1HLED G17	355	110	210	NM	1	1	80+	6500	1,60
Capella 3HLED C24	355	110	210	NM	3	1	80+	6500	1,65
Capella 1PLED G19	355	110	210	M/NM	1	1	80+	6500	1,60
Capella 3PLED C25	355	110	210	M/NM	3	1	80+	6500	1,65
Capella 1HLED G17 TEST	355	110	210	NM	1	1	80+	6500	1,60
Capella 3HLED C24 TEST	355	110	210	NM	3	1	80+	6500	1,65
Capella 1PLED G19 TEST	355	110	210	M/NM	1	1	80+	6500	1,60
Capella 3PLED C25 TEST	355	110	210	M/NM	3	1	80+	6500	1,65
Capella 1HLED G17 AUT	355	110	210	NM	1	1	80+	6500	1,60
Capella 3HLED C24 AUT	355	110	210	NM	3	1	80+	6500	1,65
Capella 1PLED G19 AUT	355	110	210	M/NM	1	1	80+	6500	1,60
Capella 3PLED C25 AUT	355	110	210	M/NM	3	1	80+	6500	1,65
Capella CEBLED C340	355	110	210	CEB	x	1	80+	6500	1,60

*M-maintained (with an option of connecting as non-maintained), NM- non-maintained, system power and output indicates data in emergency mode, tolerance range for optical and electrical data: ±10%, values apply to an ambient temperature of 25°C

Available options:

DALI	Driver with DALI interface	CLV	Fitting to low voltage central battery system CEBLV
*note - DALI option is applicable for models: G19, G25		EMS	Fitting to emergency monitoring system
TEST	Manual test button	WHITE	White steel body
AUT	Autonomous testing system		
CEB	Fitting to central battery system		