


GEMINI LED

Emergency Lighting



Images for the product family and options:



Description: Surface mounted LED emergency exit sign / escape luminaire
 Light distribution type: direct
 Optical system: clear polycarbonate diffuser, impact resistant
 Housing: polycarbonate, with test button
 Colour: white
 Battery charging time: 24 hours
 Battery: NiCd
 Recognition distance: 16 meters

General data: Mains voltage: 220-240V, 50-60Hz
 LED lifetime, h: 50000/L70B50
 SDCM: 5
 Protection class IEC: I
 Ingress protection code: IP65
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta 0...+40

Installation: On the wall. Push-in terminal, 4x2x2.5mm²

Environment: Indoor

Application: Emergency exit sign, escape route lighting



Supplied with universal sticker.

| Product | Length, mm | Width, mm | Height, mm | Illuminati on mode | Emergency operating time, h | Power in emergency mode, W* | CRI * | CCT*, K | Weight, kg |
|----------------------------|------------|-----------|------------|--------------------|-----------------------------|-----------------------------|-------|---------|------------|
| Gemini 3PLED D549 CLR TEST | 276 | 110 | 60 | M/NM | 3 | 3 | 70+ | 6000 | 0,5 |

*-M-maintained (with an option of connecting as non-maintained), NM- non-maintained, system power and output indicates data in emergency mode, tolerance range for optical and electrical data: ±10%, values apply to an ambient temperature of 25°C

Available accessories:



Product: Pictogram "Fire hose reel" Gemini LED
 Description: Pictogram "Fire hose reel" for Gemini LED

Applications:

