


HYDRA LED

Emergency Lighting



Images for the product family and options:



Description:

Surface mounted double-sided LED emergency exit sign
 Light distribution type: direct
 Optical system: opal polycarbonate diffuser, impact resistant
 Housing: polycarbonate, with test button
 Colour: white
 Battery charging time: 24 hours
 Battery: LiFePO4
 Recognition distance: 20 meters

General data:

Mains voltage: 220-240V, 50-60Hz
 LED lifetime, h: 50000/L70B50
 SDCM: 5
 Operating temperature range, °C: ta 0...+40
 Protection class IEC: I
 Ingress protection code: IP65
 Mechanical impact resistance: IK08

Installation:

On the ceiling. Push-in terminal, 3x2x2.5mm²

Environment:

Indoor

Application:

Emergency exit sign



Supplied with universal sticker.

Product	Length, mm	Width, mm	Height, mm	Illumination mode	Emergency operating time, h	Power in emergency mode, W*	CRI *	CCT*, K	Weight, kg
Hydra 3PLED G119 TEST	350	110	220	M/NM	3	1	70+	6000	1,7
Hydra 3PLED G119 AUT	350	110	220	M/NM	3	1	70+	6000	1,7

*-M-maintained (with an option of connecting as non-maintained), NM- non-maintained, system power and output indicates data in emergency mode, tolerance range for optical and electrical data: ±10%, values apply to an ambient temperature of 25°C

Available accessories:



Product: Pictogram "Fire hose reel" Libra/Hydra LED
 Description: Pictogram "Fire hose reel" for Libra/Hydra LED