


# LEPORIS C LED

## Emergency Lighting



**Images for the product family and options:**



**Description:**

Surface mounted double-sided LED emergency exit sign / escape luminaire  
 Light distribution type: omnidirectional  
 Optical system: clear PMMA diffuser  
 Housing: polycarbonate  
 Colour: white  
 Battery charging time: 24 hours (12 hours optional: AUT)  
 Battery: NiCd (LiFePO<sub>4</sub> optional: AUT), deep discharge protection  
 Recognition distance: 30 meters

**General data:**

Mains voltage: 220-240V, 50-60Hz  
 LED lifetime, h: 50000/L80B50  
 SDCM: 3  
 Protection class IEC: II  
 Ingress protection code: IP40  
 Mechanical impact resistance: IK05  
 Operating temperature range, °C: ta 0...+40

**Installation:**

On the ceiling. Push-in terminal, 3x2x2.5mm<sup>2</sup>

**Environment:**

Indoor

**Application:**

Emergency exit sign, escape route lighting



Supplied with universal sticker kit.

Product	Length, mm	Width, mm	Height, mm	Illumination mode	Emergency operating time, h	Power in emergency mode, W*	CRI *	CCT, K*	Weight, kg
Leporis C 1PLED G071	337	72	224	M/NM	1	1	80+	6500	1,35
Leporis C 3PLED G072	337	72	224	M/NM	3	1	80+	6500	1,40
Leporis C 1PLED G071 TEST	337	72	224	M/NM	1	1	80+	6500	1,35
Leporis C 3PLED G072 TEST	337	72	224	M/NM	3	1	80+	6500	1,40
Leporis C 1PLED G071 AUT	337	72	224	M/NM	1	1	80+	6500	1,35
Leporis C 3PLED G072 AUT	337	72	224	M/NM	3	1	80+	6500	1,40
Leporis C CEBLED G073	337	72	224	CEB	-	1	80+	6500	1,40
Leporis C 1PLED G082 2CLR AUT	337	72	224	M/NM	1	3	80+	6500	1,35
Leporis C 3PLED G083 2CLR AUT	337	72	224	M/NM	3	3	80+	6500	1,40
Leporis C CEBLED G084 2CLR	337	72	224	CEB	-	3	80+	6500	1,40

\*-M-maintained (with an option of connecting as non-maintained), NM- non-maintained, system power and output indicates data in emergency mode, tolerance range for optical and electrical data: ±10%, values apply to an ambient temperature of 25°C

## TECHNICAL DATA SHEET

---

**Available options:**

DALI Driver with DALI interface

*\*note - DALI option is applicable for models: G071, G072*

TEST Manual test button

AUT Autonomous testing system

CEB Fitting to central battery system

CLV

EMS

LGREY

BLACK

Fitting to low voltage central battery system CEBLV

Fitting to emergency monitoring system

Light grey thermoplastic body

Black thermoplastic body