


LEPUS S LED

Emergency Lighting



Images for the product family and options:



Description: Wall-mounted LED emergency exit sign / escape luminaire
 Light distribution type: direct
 Optical system: clear PMMA diffuser
 Housing: polycarbonate
 Colour: white
 Battery charging time: 24 hours (12 hours optional: AUT)
 Battery: NiCd (LiFePO₄ optional: AUT), deep discharge protection
 Recognition distance: 30 meters

General data: Mains voltage: 220-240V, 50-60Hz
 LED lifetime, h: 50000/L80B50
 SDCM: 3
 Protection class IEC: II
 Ingress protection code: IP40
 Mechanical impact resistance: IK05
 Operating temperature range, °C: ta 0...+40 (CEBLED ta-25...+50)

Installation: On the wall. Push-in terminal, 3x2x2.5mm²

Environment: Indoor

Application: Emergency exit sign, escape route lighting



Supplied with universal sticker kit.

| Product | Length, mm | Width, mm | Height, mm | Illumination mode | Emergency operating time, h | Power in emergency mode, W* | CRI * | CCT, K* | Weight, kg |
|-----------------------------|------------|-----------|------------|-------------------|-----------------------------|-----------------------------|-------|---------|------------|
| Lepus S 1PLED G061 | 337 | 57 | 189 | M/NM | 1 | 1 | 80+ | 6500 | 1,15 |
| Lepus S 3PLED G062 | 337 | 57 | 189 | M/NM | 3 | 1 | 80+ | 6500 | 1,20 |
| Lepus S 1PLED G061 TEST | 337 | 57 | 189 | M/NM | 1 | 1 | 80+ | 6500 | 1,15 |
| Lepus S 3PLED G062 TEST | 337 | 57 | 189 | M/NM | 3 | 1 | 80+ | 6500 | 1,20 |
| Lepus S 1PLED G061 AUT | 337 | 57 | 189 | M/NM | 1 | 1 | 80+ | 6500 | 1,15 |
| Lepus S 3PLED G062 AUT | 337 | 57 | 189 | M/NM | 3 | 1 | 80+ | 6500 | 1,20 |
| Lepus S CEBLED G063 | 337 | 57 | 189 | CEB | - | 1 | 80+ | 6500 | 1,10 |
| Lepus S 1PLED E996 2CLR AUT | 337 | 57 | 189 | M/NM | 1 | 3 | 80+ | 6500 | 1,15 |
| Lepus S 3PLED E997 2CLR AUT | 337 | 57 | 189 | M/NM | 3 | 3 | 80+ | 6500 | 1,20 |
| Lepus S CEBLED E998 2CLR | 337 | 57 | 189 | CEB | - | 3 | 80+ | 6500 | 1,10 |

*M-maintained (with an option of connecting as non-maintained), NM- non-maintained, system power and output indicates data in emergency mode, tolerance range for optical and electrical data: ±10%, values apply to an ambient temperature of 25°C

Available options:

- | | | | |
|------|-----------------------------------|-------|---|
| DALI | Driver with DALI interface | CLV | Fitting to low voltage central battery system CEBLV |
| TEST | Manual test button | EMS | Fitting to emergency monitoring system |
| AUT | Autonomous testing system | LGREY | Light grey thermoplastic body |
| CEB | Fitting to central battery system | BLACK | Black thermoplastic body |