


NASHI S LED

Emergency Lighting



Description: Surface mounted double-sided LED emergency exit sign
 Light distribution type: omnidirectional
 Optical system: clear PMMA diffuser
 Housing: polycarbonate
 Colour: white
 Battery charging time: 24 hours (12 hours optional: AUT)
 Battery: NiCd (LiFePO₄ optional: AUT), deep discharge protection
 Recognition distance: 25 meters

General data: Mains voltage: 220-240V, 50-60Hz
 LED lifetime, h: 50000/L80B50
 SDCM: 3
 Protection class IEC: II
 Ingress protection code: IP44
 Mechanical impact resistance: IK02
 Operating temperature range, °C: ta 0...+40

Installation: On the ceiling, wall or suspended (suspension kit to be ordered separately). Screw terminal, 3x2x2.5mm²

Environment: Indoor

Application: Emergency exit sign



Supplied with universal sticker kit.

Product	Length, mm	Width, mm	Height, mm	Illumination mode	Emergency operating time, h	Power in emergency mode, W*	CRI *	CCT, K*	Weight, kg
Nashi S 3PLED C434 TEST	299	43	206	M/NM	3	1	80+	6500	1,20
Nashi S 3PLED C434 AUT	299	43	206	M/NM	3	1	80+	6500	1,20
Nashi S CEBLED C435	299	43	206	CEB	-	1	80+	6500	1,00

*-M-maintained (with an option of connecting as non-maintained), NM- non-maintained, system power and output indicates data in emergency mode, tolerance range for optical and electrical data: ±10%, values apply to an ambient temperature of 25°C

Available options:

TEST	Manual test button	EMS	Fitting to emergency monitoring system
AUT	Autonomous testing system	LGREY	Light grey thermoplastic body
CEB	Fitting to central battery system	BLACK	Black thermoplastic body
CLV	Fitting to low voltage central battery system CEBLV		

Accessories:



Product: Suspension MTG KIT Nashi/Taurus LED (B/W)
 Description: Suspension wire set, 1.5m adjustable (2pcs), black/ white



Product: Suspension MTG KIT Nashi/Taurus LED (B/W)
 Description: Suspension wire set, 3m adjustable (2pcs), black/ white

Applications:

