


TAURUS LED

Emergency Lighting



Description: Surface mounted double-sided LED emergency exit sign
 Light distribution type: omnidirectional
 Optical system: clear PMMA diffuser
 Housing: extruded aluminium
 Colour: light grey
 Battery charging time: 24 hours (12 hours optional: AUT)
 Battery: NiCd (LiFePO₄ optional: AUT), deep discharge protection
 Recognition distance: 30 meters

General data: Mains voltage: 220-240V, 50/60Hz
 LED lifetime, h: 50000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP41
 Mechanical impact resistance: IK02
 Operating temperature range, °C: ta 0...+40

Installation: On the ceiling or wall (mounting brackets included), or suspended (requires an accessory). Push-in terminal, 4x2x2.5mm²

Environment: Indoor

Application: Emergency exit sign



Supplied with universal sticker kit.

Product	Length, mm	Width, mm	Height, mm	Illumination mode	Emergency operating time, h	Power in emergency mode, W*	CRI *	CCT, K*	Weight, kg
Taurus 1HLED G05 Deluxe	315	48	243	NM	1	1	80+	6500	1,25
Taurus 3HLED G07 Deluxe	315	48	243	NM	3	1	80+	6500	1,30
Taurus 1PLED G08 Deluxe	315	48	243	M/NM	1	1	80+	6500	1,20
Taurus 3PLED G10 Deluxe	315	48	243	M/NM	3	1	80+	6500	1,25
Taurus 1HLED G05 Deluxe TEST	315	48	243	NM	1	1	80+	6500	1,25
Taurus 3HLED G07 Deluxe TEST	315	48	243	NM	3	1	80+	6500	1,30
Taurus 1PLED G08 Deluxe TEST	315	48	243	M/NM	1	1	80+	6500	1,20
Taurus 3PLED G10 Deluxe TEST	315	48	243	M/NM	3	1	80+	6500	1,25
Taurus 1PLED G08 Deluxe AUT	315	48	243	M/NM	1	1	80+	6500	1,20
Taurus 3PLED G10 Deluxe AUT	315	48	243	M/NM	3	1	80+	6500	1,25
Taurus CEBLED C339 Deluxe	315	48	243	CEB	-	1	80+	6500	1,25

*-M-maintained (with an option of connecting as non-maintained), NM- non-maintained, system power and output indicates data in emergency mode, tolerance range for optical and electrical data: ±10%, values apply to an ambient temperature of 25°C

Available options:

DALI Driver with DALI interface
 *note - DALI option is applicable for models: G08, G10
 TEST Manual test button
 AUT Autonomous testing system

CEB Fitting to central battery system
 CLV Fitting to low voltage central battery system
 EMS Fitting to emergency monitoring system
 BLACK Black aluminium body

Accessories:



Product: Suspension MTG KIT Nashi/Taurus LED (B/W)
 Description: Suspension wire set, 1.5m adjustable (2pcs), black/ white



Product: Suspension MTG KIT Nashi/Taurus LED (B/W)
 Description: Suspension wire set, 3m adjustable (2pcs), black/ white