


## ANTLIA T LED

### Spotlights



Images for the product family and options:



**Description:**

Track mounted LED downlight  
 Light distribution type: direct  
 Optical system: opal polycarbonate diffuser  
 Housing: aluminium  
 Colour: white (RAL9016), black (RAL9005)

**General data:**

Mains voltage: 220-240V, 0/50-60Hz  
 LED lifetime, h: 50000/L80B50 (75000/L80B50 low power versions)  
 SDCM: 3  
 Protection class IEC: I  
 Ingress protection code: IP20  
 Mechanical impact resistance: IK02  
 Operating temperature range, °C: ta 0...+35

**Installation:**

In 3-phase track. Track adaptor (3-phase + N) with phase selector

**Environment:**

Indoor

**Application:**

Retail, showroom, exhibition, public place

| Product                         | Length, mm | Width, mm | Height, mm | Luminaire output*, lm | System power*, W | System efficacy*, lm/W | CRI* (Ra) | CCT*, K | Weight, kg |
|---------------------------------|------------|-----------|------------|-----------------------|------------------|------------------------|-----------|---------|------------|
| Antlia T LED1x1450 D948 T830 OP | 200        | 200       | 150        | 1382                  | 11,7             | 118                    | 80+       | 3000    | 1,0        |
| Antlia T LED1x2000 D949 T830 OP | 200        | 200       | 150        | 1936                  | 16,2             | 120                    | 80+       | 3000    | 1,0        |
| Antlia T LED1x2700 D950 T830 OP | 200        | 200       | 150        | 2635                  | 23,0             | 114                    | 80+       | 3000    | 1,0        |
| Antlia T LED1x1450 D948 T840 OP | 200        | 200       | 150        | 1443                  | 11,7             | 123                    | 80+       | 4000    | 1,0        |
| Antlia T LED1x2000 D949 T840 OP | 200        | 200       | 150        | 2023                  | 16,2             | 125                    | 80+       | 4000    | 1,0        |
| Antlia T LED1x2700 D950 T840 OP | 200        | 200       | 150        | 2753                  | 23,0             | 120                    | 80+       | 4000    | 1,0        |

\*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

**Available options:**

T830 Colour temperature 3000K, CRI 80+  
 T840 Colour temperature 4000K, CRI 80+  
 DALI Driver with DALI interface  
 \*note - for this model DALI option is not compatible with switch-control dimming functionality.

RAL RAL colour  
 \*note - standard tracks and adapters RAL colours: RAL9010, RAL9005, RAL7035  
 \*note - price for uncommon RAL colour could be different from indicated. Ask before placing an order

