


APUS LED

Outdoor Accent Lighting



Images for the product family and options:



Description: Surface or ground-mounted LED luminaire
 Light distribution type: direct
 Optical system: tempered glass diffuser, impact resistant
 Housing: aluminium
 Colour: dark grey (RAL7043)

General data: Mains voltage: 220-240V, 50-60Hz
 Protection class IEC: I
 Ingress protection code: IP65
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta -25...+40

Installation: On the horizontal or vertical surface, on the ground or in the ground. Cable, 0.35m, 3x1.0mm²

Environment: Outdoor

Application: Facade illumination, park, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Apus 1GU10 O11 HOL	98	98	98						0,5
Apus 1GU10 O12 GRO	98	98	98						1,4
Apus LED1x400 G872 T830 HOL L40	98	98	98	375	4,2	89	80+	3000	0,5
Apus LED1x400 G873 T830 GRO L40	98	98	98	375	4,2	89	80+	3000	1,4
Apus LED1x400 G872 T840 HOL L40	98	98	98	392	4,2	93	80+	4000	0,5
Apus LED1x400 G873 T840 GRO L40	98	98	98	392	4,2	93	80+	4000	1,4

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

T830	Colour temperature 3000K, CRI 80+	HOL	Holder for wall-mounted version
T840	Colour temperature 4000K, CRI 80+	GRO	Ground spike for ground-mounted version
L40	LED bulb with 40 beam angle	RAL	RAL colour
LOUVER	Decorative louver		

L40

