


ARCTURUS B LED

Outdoor Accent Lighting



Images for the product family and options:



Description:	Surface mounted anti-vandal LED bulkhead Light distribution type: direct Optical system: opal prismatic polycarbonate diffuser, impact resistant Housing: aluminium Colour: black (RAL9005S)
General data:	Mains voltage: 220-240V, 50/60Hz LED lifetime, h: 54000/L90B50 SDCM: 5 Protection class IEC: I Ingress protection code: IP65 Mechanical impact resistance: IK08 Operating temperature range, °C: ta -20...+35 C
Installation:	On the wall. Push-in terminal, 3x2x2.5mm2
Environment:	Outdoor
Application:	Facade illumination, transport terminal, parking area, fuel station, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Arcturus B LED1x3200 G926 T830/40/50	290	289	98	3250	25,0	130	80+	3000/ 4000/ 5000	2,1

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

- EM3 Emergency version 3 hours
- EM3B Emergency version 3 hours (best available technology)
- EM3A Emergency version equipped with an autonomous testing system, 3 hours
- *note - Operating temperature range for Luminaires with EM option, C: ta 0... +30
- EM3Atim-25 Emergency version equipped with an autonomous testing system, 3 hours. Suitable for low ambient temperatures up to -25°C

