


ARCTURUS LED

Outdoor Accent Lighting



Description: Surface mounted anti-vandal LED bulkhead
 Light distribution type: direct
 Optical system: opal polycarbonate diffuser, impact resistant
 Housing: aluminium
 Colour: black (RAL9005)

General data: Mains voltage: 220-240V, 50/60Hz
 LED lifetime, h: 50000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP65
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta -25...+40

Installation: On the wall. Push-in terminal, 3x2x2.5mm²

Environment: Outdoor

Application: Facade illumination, transport terminal, parking area, fuel station, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Arcturus LED1x2800 E054 T830 OP	308	264	182	2639	27,1	97	80+	3000	2,40
Arcturus LED1x4000 E055 T830 OP	308	264	182	3845	40,7	95	80+	3000	2,40
Arcturus LED1x2800 E054 T840 OP	308	264	182	2720	27,1	100	80+	4000	2,40
Arcturus LED1x4000 E055 T840 OP	308	264	182	3964	40,7	97	80+	4000	2,40
Arcturus LED1x2800 E054 T850 OP	308	264	182	2759	27,1	102	80+	5000	2,40
Arcturus LED1x4000 E055 T850 OP	308	264	182	4020	40,7	99	80+	5000	2,40

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

DALI	Driver with DALI interface and switch-control dimming	T830	Colour temperature 3000K, CRI 80+
MW	MW sensor	T840	Colour temperature 4000K, CRI 80+
	*note - in outdoor environment frequently moving objects (eg. trees, bushes, flags) can impact MW sensor operation	T850	Colour temperature 5000K, CRI 80+
OP	Opal polycarbonate diffuser		

