


DUBHE LED

Outdoor Accent Lighting



Images for the product family and options:



Description: Surface mounted accent LED luminaire
 Light distribution type: direct
 Optical system: opal polycarbonate diffuser, UV stable, impact resistant
 Housing: aluminium
 Colour: dark grey (RAL7043)

General data: Mains voltage: 220-240V, 50/60Hz
 LED lifetime, h: 50000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP54
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta -25...+40

Installation: On the wall or ceiling. Push-in terminal, 3x2x2.5mm2

Environment: Outdoor

Application: Facade illumination, parking area, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Dubhe S 1E27 C420	190	190	60						1,10
Dubhe S 1E27 C420 LOUVER	190	190	65						1,20
Dubhe M 1E27 C423	270	270	80						1,30
Dubhe M LED1x900 D052 T830	270	270	80	798	10,0	80	80+	3000	1,40
Dubhe M LED1x900 D052 T840	270	270	80	835	10,0	83	80+	4000	1,40
Dubhe M 1E27 C423 LOUVER	270	270	85						1,50
Dubhe M LED1x500 D053 T830 LOUVER	270	270	85	430	7,3	59	80+	3000	1,60
Dubhe M LED1x500 D053 T840 LOUVER	270	270	85	451	7,3	62	80+	4000	1,60

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

- MW MW sensor
- LOUVER Decorative louver
- RAL RAL colour
- T830 Colour temperature 3000K, CRI 80+
- T840 Colour temperature 4000K, CRI 80+

