


ETA LED

Outdoor Accent Lighting



Images for the product family and options:



Description: Surface mounted accent LED luminaire
 Light distribution type: direct
 Optical system: opal polycarbonate diffuser, UV stable, impact resistant
 Housing: aluminium
 Colour: dark grey (RAL7043)

General data: Mains voltage: 220-240V, 0/50/60Hz
 LED lifetime, h: 100000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP65
 Mechanical impact resistance: IK10
 Operating temperature range, °C: ta -20...+40/ -25...+35

Installation: On the walls or ceiling. Push-in terminal, 3x2x2.5mm²

Environment: Outdoor

Application: Facade illumination, parking area, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Eta M 1E27 C404	265	265	90						1,60
Eta M LED1x1200 D036 T830	265	265	90	1092	14,3	76	80+	3000	1,52
Eta M LED1x1200 D036 T840	265	265	90	1143	14,3	80	80+	4000	1,52
Eta M 1E27 C404 LOUVER	265	265	100						1,90
Eta M LED1x700 D037 T830 LOUVER	265	265	100	669	11,0	61	80+	3000	1,76
Eta M LED1x700 D037 T840 LOUVER	265	265	100	700	11,0	63	80+	4000	1,76
Eta B 1E27 Q78	360	360	130						2,40
Eta B 2E27 S53	360	360	130						2,40
Eta B LED1x1300 D057 T830	360	360	130	1112	13,8	81	80+	3000	3,04
Eta B LED1x1800 D038 T830	360	360	130	1529	19,5	78	80+	3000	3,04
Eta B LED1x2000 G919 T830	360	360	130	1868	23,6	79	80+	3000	3,04
Eta B LED1x1300 D057 T840	360	360	130	1164	13,8	84	80+	4000	3,04
Eta B LED1x1800 D038 T840	360	360	130	1600	19,5	82	80+	4000	3,04
Eta B LED1x2000 G919 T840	360	360	130	1956	23,6	83	80+	4000	3,04
Eta B 1E27 Q78 LOUVER	360	360	145						2,50
Eta B 2E27 S53 LOUVER	360	360	145						2,50
Eta B LED1x700 D051 T830 LOUVER	360	360	145	556	10,2	55	80+	3000	3,24
Eta B LED1x1000 D039 T830 LOUVER	360	360	145	764	14,3	53	80+	3000	3,24
Eta B LED1x700 D051 T840 LOUVER	360	360	145	582	10,2	57	80+	4000	3,24
Eta B LED1x1000 D039 T840 LOUVER	360	360	145	800	14,3	56	80+	4000	3,24

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification


TECHNICAL DATA SHEET

Available options:

- DALI Driver with DALI interface and switch-control dimming
- MW Integrated microwave (MW) motion sensor with on-off control
- *note - in outdoor environment frequently moving objects (eg. trees, bushes, flags) can impact MW sensor operation*
- *note - MW option is not compatible with LOUVER models and EM options*
- EM3B Emergency version 3 hours (best available technology)
- EM3A Emergency version equipped with an autonomous testing system, 3 hours
- EM3D Emergency version 3 hours with DALI interface
- *note - Operating temperature range for Luminaires with EM option: ta 0... +35*

- RAL RAL colour
- *note - price for uncommon RAL colour could be different from indicated. Ask before placing an order*
- T830 Colour temperature 3000K, CRI 80+
- T840 Colour temperature 4000K, CRI 80+

STANDARD



LOUVER

