


KAPPA LED

Outdoor Accent Lighting



Images for the product family and options:



Description: Surface mounted accent LED luminaire
 Light distribution type: direct
 Optical system: tempered glass diffuser, impact resistant
 Housing: aluminium
 Colour: dark grey (RAL7043)

General data: Mains voltage: 220-240V, 50-60Hz
 Protection class IEC: I
 Ingress protection code: IP65
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta -25...+40

Installation: On the wall. Screw terminal, 3x2.5mm²

Environment: Outdoor

Application: Facade illumination

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Kappa 1GU10 Q87	70	150	210						0,7
Kappa 1GU10 Q88 LONG	70	150	605						1,2
Kappa LED1x400 G870 T830 L40	70	150	210	380	4,2	90	80+	3000	1,4
Kappa LED1x400 G871 T830 LONG L40	70	150	605	380	4,2	90	80+	3000	1,4
Kappa LED1x400 G870 T840 L40	70	150	210	397	4,2	95	80+	4000	1,4
Kappa LED1x400 G871 T840 LONG L40	70	150	605	397	4,2	95	80+	4000	1,4

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

T830 Colour temperature 3000K, CRI 80+
 T840 Colour temperature 4000K, CRI 80+

L40
 RAL

LED bulb with 40 beam angle
 RAL colour

