


# OVAL LED

## Outdoor Accent Lighting



**Images for the product family and options:**



**Description:** Surface mounted anti-vandal LED bulkhead  
 Light distribution type: direct  
 Optical system: opal polycarbonate diffuser, UV stable, impact resistant  
 Housing: aluminium  
 Colour: dark grey (RAL 7043)

**General data:** Mains voltage: 220-240V, 50/60Hz  
 LED lifetime, h: 50000/L80B50  
 SDCM: 3  
 Protection class IEC: I  
 Ingress protection code: IP54  
 Mechanical impact resistance: IK08  
 Operating temperature range, °C: ta -25...+40

**Installation:** On the wall. Push-in terminal, 3x2x2.5mm<sup>2</sup>

**Environment:** Outdoor

**Application:** Facade illumination, parking area, public space


Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Oval B LED1x900 D055 T830	280	185	95	798	10,0	80	80+	3000	1,50
Oval B LED1x700 D054 T840	280	185	95	603	7,0	86	80+	4000	1,50
Oval B LED1x900 D055 T840	280	185	95	835	10,0	83	80+	4000	1,50
Oval B LED1x500 D056 T830 LOUVER	280	185	95	430	7,3	59	80+	3000	1,60
Oval B LED1x500 D056 T840 LOUVER	280	185	95	451	7,3	62	80+	4000	1,60

\*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

**Available options:**

LOUVER	Decorative louver	RAL	RAL colour
IP65	Water and dust protection IP65	T830	Colour temperature 3000K, CRI 80+
		T840	Colour temperature 4000K, CRI 80+

**STANDARD**



**LOUVER**

