


THETA LED

Outdoor Accent Lighting



Images for the product family and options:



Description: Recessed wall-mounted accent LED luminaire
 Light distribution type: direct
 Optical system: frosted tempered glass diffuser, impact resistant
 Housing: aluminium
 Colour: dark grey (RAL 7043)

General data: Mains voltage: 220-240V, 50/60Hz
 LED lifetime, h: 50000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP54
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta -25...+40

Installation: On the wall. Push-in terminal, 3x2x2.5mm²

Environment: Outdoor

Application: Facade illumination, underground passage, park, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Theta 1E27 Q75	255	80	70						1
Theta LED1x300 D058 T830	255	80	70	222	3,6	62	80+	3000	1,20
Theta LED1x300 D058 T840	255	80	70	232	3,6	64	80+	4000	1,20
Theta 1E27 Q75 GRID	255	80	70						1
Theta LED1x300 D058 T830 GRID	255	80	70	111	3,6	31	80+	3000	1,20
Theta LED1x300 D058 T840 GRID	255	80	70	116	3,6	32	80+	4000	1,20

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

GRID Protective grid T830 Colour temperature 3000K, CRI 80+
 RAL RAL colour T840 Colour temperature 4000K, CRI 80+

STANDARD

